

TWO STROKE FORMULA INJECTION

Description

Triboron is a unique, patented technology for reducing mechanical friction.

The Triboron Technology interacts with the metal surfaces and forms a tribo-film layer that reduces friction coefficient with up to 50% and protects mechanical parts from wear.

In addition to sustainable fuel savings of up to 10%, Triboron also reduces harmful emissions of carbon monoxide CO and hydrocarbons HC with up to 25%.

Verified results in real-life and laboratory tests. The Boron compounds and the substances used in the production process are harmless for nature.

Properties

- Keeps the injection system clean, maintaining efficacy and emission control.
- Prevents buildup of carbon deposits from the intake valves and in the combustion chamber.
- Reduces pollutant emissions and soot.
- Reduced fuel consumption.
- Wear & corrosion resistance.

Technical Data	
Odor	Petroleum.
Color	Yellowish
Relative density	0,806 g/cm ³
Flashpoint	> 76 °C

Areas of application

Usage: To be mixed with petrol for use in all types of 2 stroke engines powered with petrol. For injection.

Handling

Mixture procedure: Same oil content recommended by engine producer (i.e. 1:50 when 2% is recommended).

Interval: Each refueling.

Given information is based on thorough research and third part testing

Patent protected.

Produced according to

